imageFORCE
C1743F/C1743P
C1752F/C1752P



imageFORCE C1743F

imageFORCE C1743P

SPECIFICATIONS

Main Unit

Technology/Type	C1743F/C1752F: Laser/A4 Color Multifunction Printer C1743P/C1752P: Laser/A4 Color Single-function Printer
Core Functions	C1743F/C1752F: Print, Copy, Scan, Send, and Fax C1743P/C1752P: Print
Control Panel	C1743F/C1752F: 7 inch TFT LCD WVGA Color Touch Panel C1743P/C1752P: 5 Line LCD
Memory	C1743F/C1752F: 2.5 GB RAM C1743P/C1752P: 2.0 GB RAM
Processor	1.6 GHz Dual Core, 800 MHz Single core
Storage	C1743F/C1752F: 64 GB eMMC (available space 30 GB) C1743P/C1752P: 32 GB eMMC (available space 15 GB)
Interface Connections	C1743F/C1752F: NETWORK Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) OTHERS Standard: USB 2.0 (Host) x2, USB 2.0 (Device) x1
	C1743P/C1752P: NETWORK Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) OTHERS Standard: USB 2.0 (Host) x1, USB 2.0 (Device) x1
Paper Sources (Letter, 20 lb. Bond)	Standard: 550-Sheet Paper Cassette, 100-sheet Multi-Purpose Tray Optional: 550-Sheet Paper Cassettes (Cassette Feeding Unit-BA1), 550-Sheet (2 x Cassette Module-AL1)
Paper Capacity (Letter, 20 lb. Bond)	Standard: 650 Sheets Maximum: 2,300 Sheets
Output Capacity (Letter, 20 lb. Bond)	Standard: 400 Sheets Maximum: 400 Sheets

Finishing Capabilities	Collate, Group
Supported Media Types	Paper Cassette: Thin, Plain, Recycled, Color, Heavy, Bond, Letterhead, Labels, Coated Paper, Pre-Punched, Letterhead Multi-Purpose Tray: Thin, Plain, Recycled, Color, Heavy, Bond, Labels, Envelope, Postcard, Letterhead
Supported Media Sizes	Paper Cassette: Letter, Legal, Statement, Executive Custom Size: 4" x 5-7/8" to 8-1/2" x 14" Multi-Purpose Tray: Letter, Legal, Statement, Executive, Index Card, Envelope: COM10, Monarch, C5, DL Custom Size: 3" x 5" to 8-1/2" x 14"
Supported Media Weights	Paper Cassettes: 16 lb. Bond to 74 lb. Cover (60 to 200 gsm)
	Multi-Purpose Tray: 16 lb. Bond to 80 lb. Cover (60 to 216 gsm)
	Duplex: 16 lb. Bond to 74 lb. Cover (60 to 200 gsm)
Warm-up Time	C1743F/C1752F: Quick Startup Mode: 4 seconds or less[1] From Sleep Mode: 10 seconds or less[2]
	C1743P/C1752P: Quick Startup Mode: 2 seconds or less[3] From Sleep Mode: 6 seconds or less[2]
Dimensions (W x D x H)	C1743F/C1752F: 19-3/4" x 23-3/4" x 25-3/8" (500 x 603 x 645 mm) C1743P/C1752P: 19-3/4" x 21-1/4" x 16-1/2" (500 x 540 x 420 mm)
Installation Space (W x D)	30-3/8" x 33-3/8" (770 x 847 mm) (Cassette and Multi-Purpose Tray Opened)
Weight	C1743F/C1752F: Approx. 97.0 lb (44 kg)[4] C1743P/C1752P: Approx. 71.4 lb (32.4 kg)[4]

SPECIFICATIONS CONTINUED

imageFORCE
C1743F/C1743P
C1752F/C1752P

Print Specifications	
Print/Copy Speed (BW and Color)	imageFORCE C1743F/C1743P: Up to 45 ppm (Letter)[5] imageFORCE C1752F/C1752P: Up to 55 ppm (Letter)[5]
First-Print-Out Time (Letter, BW/Color)	Approx. 8.16 seconds
Print Resolution (dpi)	Up to 1200 x 1200 (equivalent)
Standard Page Description Languages	Standard: UFR II, PCL6/PCL5, Adobe® PostScript®3™
Direct Print Supported File Types	PDF, EPS, TIFF/JPEG, and XPS
Printing from Mobile and Cloud	A range of mobile and cloud printing solutions is available, including industry standards (AirPrint, Mopria, IPP Everywhere), apps and cloud services[6] (Canon PRINT, Universal Print), and MEAP-based software like uniFLOW Online, depending on your requirements. Please contact your sales representative for further information.
Operating System Standard Printing	Android[7] /Windows® 10[7]/Windows® 11[7]/Chrome OS[7] /macOS (11.2.2 or later)[8] /iOS (15.2 or later)[8] /iPadOS[8]
Print Feature	Secure Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/Orientations, Toner Reduction, Poster Printing, Forced Hold Printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer
Fonts	PS: 136 Roman PCL: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S[9] (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts[10]
Operating System	UFRII: Windows® 10/11/Server 2016/Server 2019/ Server 2022/Server 2025, macOS (11.7 or later) PCL: Windows® 10/11/Server 2016/Server 2019/Server 2022/ Server 2025 PS: Windows® 10/11/Server 2016/Server 2019/Server 2022/ Server 2025, macOS (11.7 or later) PPD: Windows® 10/11, macOS (11.7 or later)
Copy Specifications[11]	
First-Copy-Out Time (Letter, BW and Color)	Approx. 6.8 seconds
Copy Resolution (dpi)	600 x 600 dpi (Platen / Default) 600 x 600 dpi (ADF) 300 x 600 dpi (ADF / Default)
Multiple Copies	Up to 9,999 copies
Magnification	Variable zoom: 25% to 400% (1% increments)
Copy Features	Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Two-sided Original, Job Build, N on 1, Sharpness, Erase Frame, Copy ID Card, Skip Blank Pages, Free Size Original, Color Mode, Reserved Copy, Copy Sample
Scan Specifications[11]	
Type	Single-Pass Duplexing Automatic Document Feeder
Document Feeder Paper Capacity	Up to 100 sheets (20 lb. Bond)
Document Feeder Supported Media Sizes	Document Feeder Media Size: Legal, Letter, Statement, Custom Size: 1-7/8" x 3-3/8" to 8-1/2" x 14"
Document Feeder Media Weights	One-Sided/Two-Sided Continuous Scanning: 11.2 lb Bond to 47.3 lb Bond (42 to 128 gsm)
Platen Scanning Size	Up to 8-1/2" x 14"

Pull Scan Specifications	Color Network ScanGear2 for both TWAIN and WIA Supported OS: Windows® 11/Server 2016/Server 2019/Server 2022/Server 2025. As of Oct. 2025.
Scan Resolution (dpi)	C1743F/C1752F: Up to 600 dpi x 600 dpi
Scan Method	Push Scan, Pull Scan, Scan to Network, Scan to USB Memory Key, Scan to Mobile Devices, Scan to Cloud (uniFLOW Online)
Scan Speed (Letter, BW and Color)	**Send (300 x 300 dpi):** Automatic Color Select "OFF": Single-Sided Scanning: 100 ipm Double-Sided Scanning: 200 ipm Automatic Color Select "ON": Single-Sided Scanning: 50 ipm Double-Sided Scanning: 100 ipm **Copy:** Scan Speed Priority (300 x 600 dpi) Single-Sided Scanning: 50 ipm Double-Sided Scanning: 100 ipm Image Quality Priority (600 x 600 dpi) Single-Sided Scanning: 30 ipm Double-Sided Scanning: 50 ipm
Send Specifications[11]	
Destination	Standard: E-mail/Internet FAX (SMTP), SMB, FTP, SFTP, FTPS, WebDAV Optional: Super G3 FAX
Address Book	LDAP (2,000)/Local (1,600)/Speed dial (200)
Communication Protocol	File: FTP (TCP/IP), SFTP (TCP/IP), FTPS (TCP/IP), SMB (TCP/IP), WebDAV E-mail/iFax: SMTP, POP3
File Format	TIFF (MMR), JPEG, PDF (Compact, OCR (Text Searchable), Optimize for Web, PDF/A-1b, Trace&Smooth, Encrypted, Device Signature, User Signature), XPS (Compact), PDF/XPS (Device Signature, User Signature), Office Open XML (PowerPoint, Word)
Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals
Fax Specifications[11]	
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)
Sending/ Receiving Size	Legal, Letter, Statement
Fax Memory	Up to 30,000 Pages (2,000 jobs)
Speed Dials	Max. 200
Group Dials/Destinations	Max. 199 Dials
Sequential Broadcast	Max. 256 Addresses
Memory Backup	Yes
Fax Features	Sender's Name (TTI), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox

SPECIFICATIONS CONTINUED

Security Specifications	
Authentication and Access Control	C1743F/C1752F: User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online/uniFLOW[12] (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Microsoft Entra ID Authentication (Password Login, Card Login), Two-Factor Authentication at LUI/RUI, Access Management System (Access Control)
	C1743P/C1752P: User Authentication (Card Login, Username and Password Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online/uniFLOW[12] (PIN Login, Card Login, Card and PIN Login), Microsoft Entra ID Authentication (Card Login), Two-Factor Authentication at RUI, Access Management System (Access Control)
Document Security	C1743F/C1752F: Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print[12]), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support)
	C1743P/C1752P: Print Security (Secure Print, Encrypted SecurePrint, Forced Hold Printing, uniFLOW Secure Print[12])
Network Security	C1743F/C1752F: TLS 1.3 (FIPS 140-3), IPSec (FIPS 140-3), IEEE802.1X authentication, SNMPv3, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/ Wireless LAN, Wired LAN/Wired LAN), WPA3 support (Wi-Fi), Enabling/Disabling (Network Applications, Remote UI, USB Interface), G3 FAX separation from LAN, USB Port separation from LAN, Scan and Send -Virus Concerns for E-mail Reception
	C1743P/C1752P: TLS 1.3 (FIPS 140-3), IPSec (FIPS 140-3), IEEE802.1X authentication, SNMPv3, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/ Wireless LAN, Wired LAN/Wired LAN), Enabling/Disabling (Network Applications, Remote UI, USB Interface), USB Port separation from LAN
Device Security	Standard Storage Initialize, Trusted Platform Module (Optional TPM 2.0), Job Log Conceal Function, Protecting MFP Software Integrity: Verify System at Startup (NIST SP800-193: Protection), Checking MFP Software Integrity & Platform Firmware Resiliency: Automatic System Recovery (NIST SP800-193: Recovery)[13], Runtime Intrusion Detection: Trellix Embedded Control[13]
Device Management and Auditing	Administrator Password, Digital Certificate And Key Management, SAN certificates, Audit Log, Cooperating with External Security Audit System (SIEM: Security Information and Event Management)[14], Security Policy Setting

Environmental Specifications	
Operating Environment	Temperature: 50 to 86°F (10 to 30°C) Humidity: 20 to 80% RH (Relative Humidity/No condensation)
Power Requirements	110-127V, 60Hz, 15A
Power Consumption	Maximum: Approx. 1,760 W Sleep mode: Approx. 1.5 W[15] Typical Electricity Consumption (TEC)[16] 120V/US imageFORCE C1743F: 0.44 kWh imageFORCE C1752F: 0.52 kWh imageFORCE C1743P: 0.45 kWh imageFORCE C1752P: 0.52 kWh
Environmental Standards	ENERGY STAR® certified EPEAT Bronze (EPEAT 2.0)
Consumables	
Toner Cartridges	Toner 1009 BK/C/M/Y (All-in-One Toner Cartridge)[17]
Toner Yield (Estimated @5.0% Coverage)	YMC: 12,000 impressions BK: 18,700 impressions
Paper Source Options[18]	
Cassette Module-AL1	Paper Capacity: 550 sheets [20 lb. bond (75 gsm)]
	Paper Type: Thin, Plain, Recycled, Coated paper, Color, Heavy, Bond, Label, Pre-Punched, Letterhead
	Paper Size: Legal, Letter, Executive, Statement, Custom Size: 4" x 5-7/8" to 8-1/2" x 14"
	Paper Weight: 16 lb bond to 74 lb cover (60 to 200 gsm)
Cassette Feeding Unit-BA1	Paper Capacity: 550 Sheets [20 lb. bond (75 gsm)]
	Paper Type: Thin, Plain, Recycled, Color, Heavy, Bond, Label, Pre-Punched, Letterhead
	Paper Size: Legal, Letter, Executive, Statement, Custom Size (4" x 5-7/8" to 8-1/2" x 14")
	Paper Weight: 16 lb bond to 74 lb cover (60 to 200 gsm)

[1] Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display.
[2] Time from exiting Sleep mode to when printing is operational.
[3] Time from device power-on until print ready (not print reservation).
[4] Includes consumables.
[5] Print speed is based on internal testing. Print speed may vary, depending on the number of copies selected as well as the settings for size, type, and orientation of paper.
[6] Subscription to a third-party cloud service required. Subject to third-party cloud service provider's Terms and Conditions.
[7] Need to select the [Use Mopria] check box [OK].
[8] Need to select the [Use AirPrint] check box [OK].
[9] Optional PCL International Font Set-A1 is required.
[10] Optional Barcode Printing Kit-D1 is required.
[11] Only applies to C1743F/C1752F model.
[12] Requires optional uniFLOW Online/uniFLOW.
[13] This feature is off by default and must be turned on by the administrator. Warm-up times are affected once turned on.
[14] Third-party SIEM system required. Subject to third-party SIEM provider's Terms and Conditions. Canon cannot ensure compatibility with all third-party SIEM systems.
[15] 1.5 W is not available in all circumstances due to certain settings.
[16] Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.2.
[17] Includes toner, drum, developer, and waste toner hopper.
[18] Paper capacity may vary with different paper types/sizes.

usa.canon.com/business

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified this model as meeting the ENERGY STAR® energy efficiency criteria through an EPA recognized certification body. ENERGY STAR® and the ENERGY STAR® mark are registered U.S. marks. Canon, imageFORCE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its security features or recommendations will prevent security issues. Customers should perform their own due diligence and consult with their security expert to determine what security features to implement for their organization. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. Some security features may impact functionality/performance; you may want to test these settings in your environment. Trellix and the Trellix logo are trademarks or registered trademarks of Musarubra US LLC or its subsidiaries in the U.S. and other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated.

All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Representative for details. Products shown with optional accessories. Subscription to a third-party cloud service required. Subject to third-party cloud service provider's terms and conditions. uniFLOW is a registered trademark of NT-ware Systemprogrammierung GmbH. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21, or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2026 Canon U.S.A., Inc. All rights reserved.

10.02.26/26-1467-16150